

ÅhusTurf AB

Sedan 2013



Technical specification | Deluxe 45



Type	: tufted non filled synthetic grass carpet
Yarn material	: PE monofilament straight, PE monofilament non directional & PP monofilament curled
Yarn type	: 16.500/24 dTex : combination of V-shape non directional, C-shape and oval shape texturized
Yarn quality	: environmental friendly, UV stabilized, UV stability meets DIN 53387 standard : free of lead and cadmium
Colour fastness	: xenon test: blue scale > 7, grey-scale > 4
Primary backing	: 100% PP Thiobac ® with fleece, black, UV stabilized : weight 155 gr/m ²
Secondary backing	: black latex compound with a base of styrene-butadiene (SBR), with drainage holes : weight 850 gr/m ²

Tuft gauge	: 3/8"	
Pile height	: 45mm	(+/-10%)
Stitches per 10cm	: 12.0	(+/-10%)
Stitches per m ²	: 12.600	(+/-10%)
Face weight	: 2.050 gr/m ²	(+/-10%)
Total weight	: 3.055 gr/m ²	(+/-10%)

Roll width	: 400cm + 200cm	(+/- 2cm)
Roll length	: 25.20 m ¹	(+/- 20cm)
	: roll length may vary	

Water permeability	: 60 liter/min/m ²
Fire retardant classification	: Cfl-S1 (EN ISO 11925-2: sand filled ca. 5mm) : Efl-S1 (EN ISO 11925-2: non filled)
Batch information	: before installation please make sure the batch numbers (AVL-....) are equal
Shrinkage	: shrinkage can appear due to high temperatures. Make sure the carpet can relax before cutting
Infill recommendation	: non infill (optional 5kg/m ²)

Avalon has the right to alter each product specification in order to improve the artificial grass according to the newest technological applications.
Avalon is not legally liable in case of non-compliance with the above mentioned specifications.